Section 1 Identification

Trade Name: LONG GONE

Product Identification: 6440

Synonyms: Detergent/fragrance

Product Use Description:

Air freshener/ deodorant

General Info Phone: (800) 795-9222 Emergency Phone: (800) 535-5053

Supplier:

HILLYARD KENTUCKY 551 B HORTON CT. 859-252-7511

LEXINGTON, KY 40511

Section 2 Hazards Identification

Classifications

Sensitization - Skin

Eye Irritation - Category 2

Skin Irritation - Category 2

Specific Target Organ Toxicity (single exposure) - Category 3

Flammable liquids - Category 2





Flammable

...

Signal Word: Warning

Hazard Statements

Keep out of reach of children.

Read label and SDS before use.

May cause an allergic skin reaction.

Causes skin and serious eye irritation.

May cause drowsiness or dizziness.

Flammable liquid and vapor.

Precautionary Statements

Prevention

Wash hands thoroughly after handling.

Wear protective gloves.

Wear eye and face protection.

Contaminated work clothing must not be allowed out of the workplace.

Avoid breathing vapors/spray. Use only in a well-ventilated area.

Keep away from heat, sparks, open flames and hot surfaces. □ -No smoking.

Use explosion-proof ventilating.

Use only non-sparking tools. Take precautionary measures against static discharge.

Keep container tightly closed.

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water/shower.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical attention.

 Trade Name:
 LONG GONE
 SDS #:
 6440
 Page 1 of 5

 SDS ID:
 SDS01993
 Revision # 1
 Revision Date 05/30/2015

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or doctor if you feel unwell.

Storage

Store locked up in a well-ventilated place.

Keep cool.

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

Section 3 Composition

		<u>Concentration</u>
Chemical Name	<u>CAS #</u>	% by Weight
Isopropanol	67-63-0	>=30 <= 40
Ethoxylated Nonylphenol	127087-87-0	>=1 <= 5
Fragrance	N/A	>=1 <= 5

Section 4 First Aid

EMERGENCY OVERVIEW

WARNING. Flammable. Keep away from heat and flame. May be harmful if swallowed. Eye and skin irritant. May cause skin sensitization.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: May be harmful if swallowed. Seek medical attention immediately.

Section 5 Fire Fighting Measures

 Trade Name:
 LONG GONE
 SDS #:
 6440
 Page 2 of 5

 SDS ID:
 SDS01993
 Revision # 1
 Revision Date
 05/30/2015

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Containers may build pressure and rupture.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

Isopropanol

ACGIH TLV 400 ppm OSHA PEL 400 ppm

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: No special requirements are needed for this material.

Engineering Controls: Good general ventilation required.

Section 9 Physical and Chemical Properties

<u>Property</u> <u>Value</u>

Appearance CLEAR LIQUID Auto Ignition Temp NOT AVAILABLE
Boiling Point NOT AVAILABLE Color COLORLESS
Decomposition Temperature NOT AVAILABLE Evaporation Rate NOT AVAILABLE

 Trade Name:
 LONG GONE
 SDS #:
 6440
 Page 3 of 5

 SDS ID:
 SDS01993
 Revision # 1
 Revision Date 05/30/2015

Explosive Limit Ranges NOT AVAILABLE NOT AVAILABLE **Explosive Properties** Flash Point 83 F Melting/Freezing Point **NOT AVAILABLE** Odor **PLEASANT** Odor Threshold **NOT AVAILABLE** Other Information VOC content (wt. %): 32 Oxidizing Properties **NOT AVAILABLE**

Partition Coeff NOT AVAILABLE Physical State LIQUID
Relative Density 1.0 Solubility (Water) COMPLETE
Vapor Density NOT AVAILABLE Vapor Pressure NOT AVAILABLE

Viscosity NOT AVAILABLE pH 7-8

Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

Chemical Stability :Stable under normal conditions.Incompatible Materials :Acids and strong oxidizers

Conditions to Avoid : High temperatures

Decomposition Products: CO, CO2

Vapors may ignite at temperatures exceeding flash point.

Section 11 Toxicological Information

Primary Route of Entry: Skin contact

Acute/Potential Health Effects:

EYES: Causes serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: Causes skin irritation. Prolonged or repeated contact may dry the skin and cause skin sensitization. Symptoms may include redness, burning, drying of skin.

INHALATION: High vapor concentrations may be irritating to respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. May cause peripheral nervous system disorder and/or damage.

INGESTION: May cause headache, dizziness, incoordination, nausea, vomiting, diarrhea and general weakness.

Chronic / Long Term Effects: May cause skin sensitization.

Target Organ Effects: Skin, central nervous system.

Reproductive/Developmental Information: No data.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Isopropanol: Inhalation: > 10,000 mg/l Exposure time: 6 h, Species: rat

Section 12 Ecological Information

Not available

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

 Trade Name:
 LONG GONE
 SDS #:
 6440
 Page 4 of 5

 SDS ID:
 SDS01993
 Revision # 1
 Revision Date 05/30/2015

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 1993

Proper shipping name Flammable liquid, n.o.s. (contains Isopropanol)

Class 3

Packing group III

Section 15 Regulatory Information

If identified components of this product are **CERCLA** hazardous substances and/or listed under <u>Sections 302, 304, or 313 of</u>
<u>Title III</u> of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under <u>California Proposition 65</u> (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic () Fire (X) Pressure () Reactive () Not Applicable ()

<u>T.S.C.A. Status:</u> All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

<u>RCRA Status:</u> Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

D001

Section 16 Other Information

HMIS Ratings:



Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 5/30/15

 Trade Name:
 LONG GONE
 SDS #:
 6440
 Page 5 of 5

 SDS ID:
 SDS01993
 Revision # 1
 Revision Date
 05/30/2015