MATERIAL SAFETY DATA SHEET



LINOSAFE LINOLEUM STRIPPER

H	IMIS	NFPA	Personal protective equipment
Health	3	3	and the second
Fire Hazard	0	0	
Reactivity	0	0	

Version Number: 3 Preparation date: 2007-04-16

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LINOSAFE LINOLEUM STRIPPER

MSDS #: 114141001

Product code: 114141X, 04188, 04428

Recommended use: Industrial/Institutional. Floor care. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier:

US Headquarters
JohnsonDiversey, Inc.

8310 16th St.
Sturtevant, Wisconsin 53177-0902

Canadian Headquarters
JohnsonDiversey - Canada, Inc.
2401 Bristol Circle
Oakville, Ontario L6H 6P1

Phone: 1-888-352-2249 MSDS Internet Address: www.johnsondiversey.com

Emergency telephone number: 1-800-851-7145 (Prosar); 1-651-917-6133 (Int'l Prosar); 01-800-710-3400 (México)

Phone: 1-800-668-3131

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principle routes of exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Eye contact: Corrosive. Causes permanent eye damage, including blindness.

Skin contact: Corrosive. May cause permanent damage.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS

Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat	LD50 Dermal -	LC50 Inhalation - Rat
ingredient(s)	CAS#	Weight /6	LD30 Oral - Nat	Rabbit	LC30 IIIIlalation - Nat
Monoethanolamine	141-43-5	1 - 5%	=1720 mg/kg	=1 mL/kg	Not available
2-butoxyethanol	111-76-2	5 - 10%	=470 mg/kg	=220 mg/kg	=2.21 mg/L (4 h)
					=450 ppm (4 h)

4. FIRST AID MEASURES

Eye contact: Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact: Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.

Inhalation: If breathing is affected, remove to fresh air. Get medical attention immediately.

Immediately drink one cupful of water or milk. DO NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious person. Call medical attendant,

medical doctor, or poison control center

Aggravated Medical Conditions: Persons with pre-existing skin disorders may be more susceptable to irritating effects

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Dry chemical, water spray, foam, carbon dioxide.

Specific hazards: None known.

Unusual hazards: Corrosive material (See sections 8 and 10).

Specific methods: No special methods required.

LINOSAFE LINOLEUM STRIPPER 1 of 4

5. FIRE-FIGHTING MEASURES

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a and clean-up methods:

water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Solubility:

Keep tightly closed in a dry, cool and well-ventilated place. Protect from freezing. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles.

Hand protection: Chemical-resistant gloves. Includes: neoprene gloves

Skin and body protection: If major exposure is possible, wear suitable protective clothing and footwear.

Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that

meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace

conditions warrant a respirator's use.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	CAS#	ACGIH	OSHA	Mexico
Monoethanolamine	141-43-5	6 ppm (STEL)	3 ppm (TWA)	6 ppm (STEL)
		3 ppm (TWA)	6 mg/m³ (TWA)	15 mg/m³ (STEL)
				3 ppm (TWA)
				8 mg/m ³ (TWA)
2-butoxyethanol	111-76-2	20 ppm (TWA)	Skin	360 mg/m ³ (STEL)
_			50 ppm (TWA)	75 ppm (STEL)
			240 mg/m ³ (TWA)	26 ppm (TWA)
				120 mg/m ³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid **Bulk density:** No information available 10.5 Dilution pH: No information available. pH: Vapor density: No information available Appearance: Aqueous solution Colourless **Evaporation Rate** No information available Color: Odor: Solvent Boiling point/range: Not determined Specific gravity: Melting point/range: Not determined 1 01

Density: 8.60 lbs/gal Decomposition temperature: Not determined VOC: 9.14% * Autoignition temperature: No information available >200°F >93.3°C Flash point: Partition coefficient (n-octanol/water): No information available

Viscosity: No information available **Elemental Phosphorus:** 0 %P

10. STABILITY AND REACTIVITY

Solubility in other solvents:

No information available

Stability: The product is stable

Polymerization: Hazardous polymerization does not occur

Hazardous decomposition products: None known Conditions to avoid: Do not freeze.

Soluble

11. TOXICOLOGICAL INFORMATION

LINOSAFE LINOLEUM STRIPPER 2 of 4

^{* -} Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

11. TOXICOLOGICAL INFORMATION

Acute toxicity Corrosive; Oral LD50 estimated to be between 500 - 5000 mg/kg

Component Information: See Section 3
Chronic toxicity: None known

Specific effects

Carcinogenic effects: None known Mutagenic effects: None known Reproductive toxicity: None known Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local applicable regulations.

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Sodium xylene sulfonate	1300-72-7	-	-	-	-
2-butoxyethanol	111-76-2	X	X	X	X
Diethylene glycol butyl ether	112-34-5	-	-	X	-
Ethylene glycol phenyl ether	122-99-6	-	-	X	-
Water	7732-18-5	-	-	-	-

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol	111-76-2	5 - 10%			X
Diethylene glycol butyl ether	112-34-5	10 - 20%			X
Ethylene glycol phenyl ether	122-99-6	5 - 10%			X

CAA HAP/CAA ODS/CWA Priority Pollutants: None

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether	X		
Ethylene glycol phenyl ether	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: Reactivity: Sudden Release of Pressure: -

Canada

WHMIS hazard class: E Corrosive material .



Ingredient(s)	CAS#	NPRI
2-butoxyethanol	111-76-2	X
Diethylene alycol butyl ether	112-34-5	X

LINOSAFE LINOLEUM STRIPPER 3 of 4

Ingredient(s)	CAS#	NPRI	
Ethylene glycol phenyl ether	122-99-6	X	

16. OTHER INFORMATION

Reason for revision:
Prepared by:
Additional advice:
Not applicable
NAPRAC
None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

LINOSAFE LINOLEUM STRIPPER

4 of 4